



# TECHNICAL DATA SHEET: PAINTS & ENAMELS



## Wallshield

1<sup>st</sup> Kote Acrylic

### FEATURES AND BENEFITS

- High cover coating
- Smooths over surface imperfections
- Interior/ Exterior



### DIRECTIONS FOR USE

### USAGE PRECAUTIONS

Read all instructions before use. Only apply to dry / damp free surfaces with a moisture content permanently less than 10%. Allow new plaster to dry for a minimum 28 days. Prime all plaster or concrete surfaces with a suitable Powafix Tradeshield Plaster primer\*. Prime wood / timber surfaces with Powafix Pink Wood Primer\*. Do not paint in cold weather below 8°C or if imminent rainfall is expected. In areas affected by heavy dew do not paint after 2pm. Do not apply coating on any contaminated or unsound surface as this will affect the adhesion. Contact our product support line on 072 396 4980 for assistance prior to painting.

### SURFACE PREPARATION

Remove all loose / flaking material with a high pressure cleaner, scraper or wire brush. Sand smooth any glossy surfaces. Treat algae or fungi with Powafix Fungi Fix\*. Thoroughly clean any surface contaminants with Powafix Sugar Soap\*. If painting on plaster or concrete fill all holes and cracks with Powafix Multi Filla all purpose crack filler\*. For deep cracks, holes and damaged plaster use Powafix Powafilla\*. For timber surfaces fill imperfections using Powafix Spackle wood filler \*. Use Powafix Powaskim\* products to treat rough / uneven surfaces prior to painting.



More than just a product.

BRAND



QUALITY



SERVICE



VALUE



# TECHNICAL DATA SHEET: PAINTS & ENAMELS



## APPLICATION INSTRUCTIONS

Stir well before use. Apply product with a brush, roller or airless spray. Coverage is 6-8m<sup>2</sup>/L, this may increase on porous or rough surfaces. Apply two coats allowing 2 – 4 hours drying time between coats. Apply a minimum of two coats and do not exceed recommended spread rate. Clean brushes with Powafix Solvent Based Brush Cleaner\*. Product thinning is not recommended.

## STORAGE INSTRUCTIONS

Ensure lid is tightly sealed and product stored upright. Secure product when transporting to prevent accidental spillage. Store in a cool place out of reach of children. Dispose of empty container and do not use for any other purpose. Do not dispose into common waste system contact 0860 254 620 for disposal information. Discard product 18 months after batch date.

## SAFETY INSTRUCTIONS



Causes mild skin irritation

Read all instructions before use. Replace lid when not in use. Use product in well ventilated areas. If medical advice is needed, have product packaging at hand. Do not eat or drink when using product. Use personal protection as required. Wear protective gloves. Wear eye protection. Wear a dust mask. Avoid inhalation of dust.

**IF IN EYES** Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Seek medical attention if symptoms persist.

**IF ON SKIN** Take off immediately all contaminated clothing and wash before reuse. Wash with soapy water. Seek medical attention if symptoms persist.

**IF SWALLOWED** Do not induce vomiting and seek immediate medical attention. Dispose of contents and packaging in accordance with all local, regional, national and international regulations. National poison centre 0861 555 777.



More than just a product.

BRAND



QUALITY



SERVICE



VALUE



# TECHNICAL DATA SHEET: PAINTS & ENAMELS



Helpline Number: 072 396 4980

## PRODUCT GAURANTEE

In the unlikely event that you are not totally satisfied. This product has a 5 year quality guarantee. This guarantee excludes product failure caused by misuse or use of the product outside of recommended uses and instructions on the packaging. This guarantee only includes replacement of the same product or a refund as specified in the terms and conditions. Product must be returned in its original packaging with proof of payment.

1. Terms and conditions apply.
2. Project must be registered with Powafix before any surface preparation and coating application commences.
3. Terms and conditions available on request.



## TECHNICAL DATA SHEET: PAINTS & ENAMELS



### PRODUCT INFORMATION

Barcode	Product Code	Colour	Packsize	Case Size	
6009600997929	CLIM1STKOTE5LWH	White	5L	2	
6009600994270	CLIM1STKOTE20LW	White	20L	1	
6009600997929	CLIM1STKOTE5LPE	Peach	5L	2	
6009600997677	CLIM1STKOTE20LPE	Peach	20L	1	
6009600997912	CLIM1STKOTE5LCR	Cream	5L	2	
6009600997660	CLIM1STKOTE20LCR	Cream	20L	1	

### PRODUCT SPECIFICATIONS

SG	1.37-1.43
Appearance	Smooth Matt
PH	8.0-9.5
Viscosity	89KU-91KU

ISSUE DATE: February 2022

The information contained on this Technical Data Sheet is, to the best of our knowledge, true and accurate. As the conditions of use are not under our control, no warranty is given or implied in respect of such information, or in respect of any recommendations or suggestions which may be made.