



More than just a product.

BRAND



QUALITY



SERVICE



VALUE



# TECHNICAL DATA SHEET: WATERPROOFERS



## POWA COAT

Acrylic Water Proofer



### FEATURES AND BENEFITS

- Effective at sealing roofing, gutters, down pipes, and parapet walls
- Durable weather resistant coating
- Free membrane included

### DIRECTIONS FOR USE

### USAGE PRECAUTIONS

Read all instructions before use. Only apply to dry surfaces with a permanent moisture content less than 10%. New plaster or concrete surfaces must cure for a minimum of 28 days and be primed with Powafix Tradeshield Plaster Primer\* prior to applying Powa Coat. Ensure there is adequate drainage to prevent ponding. Keep gutters and drainage holes clear. Do not paint in cold weather below 8°C or if imminent rainfall is expected. In areas affected by heavy dew do not paint after 2pm. Do not apply coating on any contaminated or unsound surface as this will affect the adhesion. Use corresponding batch numbers to ensure colour consistency. Contact our product support line on 072 396 4980 for assistance prior to painting.

### SURFACE PREPARATION

Remove all loose / flaking material and old waterproof coatings. Sand smooth any glossy surfaces. Use a hard bristle brush to remove all efflorescence. Treat algae and fungi with Powafix Fungi Fix\*. Thoroughly clean surface and contaminates with Powafix Sugar Soap\*. Fill all holes and cracks with Powafix Aqua Crete waterproof crack filler\*.

Loose or powdery surfaces - treat with Powafix Solvent Bonding Liquid\*.

Clay and cement roof tiles - prime with Powafix Powabond\*

Metal surfaces - thoroughly clean surfaces with Powafix Rust Mate\* and prime with Powafix Metal Primer\*. Timber surfaces - prime with Powafix Wood Primer\*.



More than just a product.

BRAND



QUALITY



SERVICE



VALUE



# TECHNICAL DATA SHEET: WATERPROOFERS



## APPLICATION INSTRUCTIONS

Thoroughly stir before use and apply product with a water proofing brush - (0.5m<sup>2</sup>/L). Measure and cut Powafix Water proofing membrane\* to the required length. Apply a base coat. Place and soak membrane in Powa Coat, squeeze out excess product and press membrane into wet base coat. Ensure all air pockets and creases are brushed out and removed. Allow 4 – 6 hours drying time between coats. Apply a minimum of three coats at 0.5m<sup>2</sup>/L. Powa Coat can be over coated with decorative coatings. Clean brushes with Powafix Solvent Based Brush Cleaner\*. Product thinning is not recommended.

## STORAGE INSTRUCTIONS

Ensure lid is tightly sealed and product stored upright. Secure product when transporting to prevent accidental spillage. Store in a cool place out of reach of children. Dispose of empty container and do not use for any other purpose. Do not dispose into common waste system contact 0860254620 for disposal information. Discard product 18 months after batch date.

## SAFETY INSTRUCTIONS



May cause allergic skin reaction.

Read all instructions before use. Replace lid when not in use. Use product in well ventilated areas. If medical advice is needed, have product packaging at hand. Do not eat or drink when using product. Use personal protection as required. Wear protective gloves. Wear eye protection. Wear a dust mask. Avoid inhalation of dust.

**IF IN EYES** Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Seek medical attention if symptoms persist.

**IF ON SKIN** Take off immediately all contaminated clothing and wash before reuse. Wash skin with soapy water. Seek medical attention if symptoms persist.

**IF SWALLOWED** Wash out mouth with water. Do not induce vomiting and seek immediate medical attention.

Dispose of contents and packaging in accordance with all local, regional, national, and international regulations. National poison centre 0861 555 777.



More than just a product.

BRAND



QUALITY



SERVICE



VALUE



# TECHNICAL DATA SHEET: WATERPROOFERS



## PRODUCT GUARANTEE

In the unlikely event that you are not totally satisfied. This product has a 5-year quality guarantee. This guarantee excludes product failure caused by misuse or use of the product outside of recommended uses and instructions on the packaging. This guarantee only includes replacement of the same product, or a refund as specified in the terms and conditions. Product must be returned in its original packaging with proof of payment.

Terms and conditions apply.

Project must be registered with Powafix before any surface preparation and coating application commences.

Terms and conditions available on request.

\*Use product directions displayed on respective products

## PRODUCT INFORMATION

Barcode	Product Code	Pack Size	Case Size
6009600999374	WATPRO1LWH	1L	6
6009600999381	WATPRO5L	5L	2



\* Available Colours: White, Grey, Charcoal, Black, Burgundy, Terracotta, Red, Green

## PRODUCT SPECIFICATION

Appearance	Smooth matt
Density	1.28-1.31
pH	8.0-9.5



More than just a product.

BRAND



QUALITY



SERVICE



VALUE



# TECHNICAL DATA SHEET: WATERPROOFERS



ISSUE DATE: December 2022

The information contained on this Technical Data Sheet is, to the best of our knowledge, true and accurate. As the conditions of use are not under our control, no warranty is given or implied in respect of such information, or in respect of any recommendations or suggestions which may be made.