



TECHNICAL DATA SHEET: PUTTY & ADHESIVES



POWA GLAZE®

FAST DRYING WINDOW PUTTY

FEATURES AND BENEFITS

- Suitable for use on both steel and timber surfaces
- Can be painted with enamels and varnish
- High adhesion and crack resistant



DIRECTIONS FOR USE

SURFACE PREPARATION

- Read all instructions before use.
- 1kg of Powa Glaze® will glaze approximately 2 metres of window frame.
- Steel frames - Remove all loose glass, putty & flaking particles. Sand smooth any high gloss surfaces and treat any rust with Powafix Rust Mate®*.
- Timber frames - Remove all loose glass, putty & flaking particles. Sand smooth any high gloss surfaces and clean surface with Powafix Sugar Soap*.
- Steel frames – Prime bare metal surfaces with a suitable metal primer.
- Timber Frame – Prime timber with Powafix Boiled Linseed Oil*.

APPLICATION INSTRUCTIONS

- Work Powa Glaze® by hand to make it smooth and easy to use.
- Before placing the glass in press Powa Glaze® into the back section of the window frame. Shape & smooth with a putty knife.
- Place in the glass and ensure it is well supported and secure. Roll Powa Glaze® into a sausage and apply around the frame on the outside of the glass & onto the metal or wooden window frame, smoothing with a putty knife.
- Prime dried Powa Glaze® white with Universal Undercoat before painting. Alkyd timber varnish can be applied directly to dried Powa Glaze® teak.
- Powa Glaze® gradually hardens over 1 - 2 days. Once surface dry coat as required.



More than just a product.

BRAND



QUALITY




SERVICE



VALUE



TECHNICAL DATA SHEET: PUTTY & ADHESIVES



USAGE PRECAUTION

Do not mix paraffin or any other solvent with Powa Glaze®. Product can be softened by adding a small amount of Powafix Raw Linseed oil.

*Use product directions displayed on respective products

STORAGE INSTRUCTIONS


Read all instructions before use. Only apply to dry surfaces with a moisture content less than 10%. Do not apply to any unprimed, contaminated, or unsound surface as this will affect the adhesion and performance. Contact our product support line on 072 396 4980 for assistance prior to use. Once opened ensure pouch is folded and tightly sealed to prolong shelf life. Secure product when transporting to prevent accidental spillage. Store product in a cool well-ventilated place away from sunlight or heat. Store locked away and out of reach of children. Dispose of empty container and do not use for any other purpose. Do not dispose into common waste system contact 0860254620 for disposal information. Discard product 6 months after batch date.

SAFETY INSTRUCTIONS

Read all instructions before use. Use product within well-ventilated areas. If medical advice is needed, have product packaging at hand. Use personal protective equipment as required. Wear protective gloves. Wear eye protection. Wear a dust mask. Avoid inhalation of dust. **IF IN EYES** flush with water. Seek medical attention if symptoms persist. **IF ON SKIN** wash with soapy water. **IF SWALLOWED** do not induce vomiting and seek immediate medical assistance. Dispose of contents and packaging in accordance with all local, regional, national and international regulations. Nation poison centre: 0861 555 777



TECHNICAL DATA SHEET: PUTTY & ADHESIVES



PRODUCT INFORMATION

Colour	Barcode	Product Code	Pack Size	Case Size	
WHITE	6009600999435	PWGLAZ1KGW	1KG	10	
TEAK	6009600999718	PWGLAZ1KGT	1KG	10	

PRODUCT SPECIFICATION

Appearance	Oily Paste
Colour	White or Teak
Drying / hardening Time	2-4 days

ISSUE DATE: NOVEMBER 2023

The information contained on this Technical Data Sheet is, to the best of our knowledge, true and accurate. As the conditions of use are not under our control, no warranty is given or implied in respect of such information, or in respect of any recommendations or suggestions which may be made.



More than just a product.

BRAND



QUALITY



SERVICE



VALUE



TECHNICAL DATA SHEET: PUTTY & ADHESIVES

