TECHNICAL DATA SHEET: BONDING LIQUIDS & PRIMERS

CLEAR GRIP

PURE ACRYLIC CLEAR SEALER



FEATURES AND BENEFITS

- ENHANCES & PROTECTS MASONRY SURFACES
- WATER- AND UV-RESISTANT DURABLE FINISH
- LONG-LASTING PROTECTION AGAINST FUNGI AND ALGAE

DIRECTIONS FOR USE

USAGE PRECAUTIONS

Read all instructions before use. Only apply to dry / damp free surfaces with a moisture content less than 10%. Prime all plaster or concrete surfaces with a suitable Powafix Plaster primer*. Only use with fresh moisture fresh cement / plaster. Do not paint in cold weather below 8°C or if imminent rainfall is expected. In areas affected by heavy dew do not paint after 2pm. Do not apply coating on any contaminated or unsound surface as this will affect the adhesion. Contact our technical help line on 072 396 4980 for assistance prior to painting.

SURFACE PREPARATION

Remove dirt, dust, grease, oil, moss, algae and loose material, Treat algae with Powafix Heavy Duty Algae Wash. Scrub with hard bristle brush using Powafix Brick & Floor Cleaner*. Rinse thoroughly with high-pressure cleaner

APPLICATION INSTRUCTIONS

IDEAL FOR:

- Paving stones and block paving
- Cement roof tiles
- Precast concrete walls
- Concrete floors and driveways
- Cement-plastered walls
- Garden pots and ornaments

TECHNICAL DATA SHEET: BONDING LIQUIDS & PRIMERS

APPLICATION INSTRUCTIONS

- Stir well before use
- Apply to dry surface using brush, roller or spray
- Apply evenly and avoid pooling
- Ensure good ventilation when used indoors
- Ensure product is fully absorbed into the surface
- Apply a minimum of 2 coats
- Allow 2–4 hours between coats

STORAGE INSTRUCTIONS

Ensure cap is tightly sealed and product stored upright. Secure product when transporting to prevent accidental spillage. Store in a cool place locked away and out of reach of children. Dispose of empty container and do not use for any other purpose. Do not dispose into common waste system contact 0860 254 620 for disposal information. Discard product 18 months after batch date.

SAFETY INSTRUCTIONS



May cause allergic skin reaction.

Read all instructions before use. Replace cap when not in use. Use product in well ventilated areas. If medical advice is needed, have product packaging at hand. Do not eat or drink when using product. Use personal protection as required. Wear protective gloves. Wear eye protection. Wear a dust mask. Avoid inhalation of dust.

IF IN EYES Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Seek medical attention if symptoms persist.

IF ON SKIN Wash skin with soapy water. Take off immediately all contaminated clothing and wash before reuse. Seek medical attention if symptoms persist.

IF SWALLOWED Rinse mouth with clean water. Do not induce vomiting and seek immediate medical attention.

Dispose of contents and packaging in accordance with all local, regional, national and international regulations.
National poison centre 0861 555 777

TECHNICAL DATA SHEET: BONDING LIQUIDS & PRIMERS

PRODUCT GUARANTEE

In the unlikely event you are not totally satisfied – this product has a 12 month warranty. This warranty only includes replacement of the same product or a refund of the original purchase price. Product must be returned unaltered, in its original packaging with proof of purchase. This warranty excludes product failure caused by misuse of product outside of recommended uses and instructions on the packaging.

ISSUE DATE: JUNE 2026

The information contained on this Technical Data Sheet is, to the best of our knowledge, true and accurate. As the conditions of use are not under our control, no warranty is given or implied in respect of such information, or in respect of any recommendations or suggestions which may be made.